




C71

Mobile Computer



Chainway C71 with abundant functions is an Android rugged mobile computer. With its powerful processor, stable wireless connections and comprehensive data capture options, you can find this easy-to-deploy device a valuable helper to increase productivity in logistics, warehousing, retail, identity verification, meter reading, IC card reading and etc.



Specification

Performance

CPU	Cortex-A53 2.3 GHz Octa-core
RAM+ROM	3 GB + 32 GB / 4 GB + 64 GB (optional)
Expansion	Supports up to 128 GB Micro SD card
Operating System	Android 11; GMS, FOTA, Soti MobiControl, SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility

Communication

WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
WWAN	2G: GSM850/GSM900/DCS1800/PCS1900 3G: WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BCO TD-SCDMA: A/F 4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/ B34/B38/B39/B40/B41
Bluetooth	Bluetooth 5.0
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Physical Characteristics

Dimensions	164.2 x 78.8 x 17.0 mm / 6.46 x 3.1 x 0.67 in. (for standard version)
Weight	288 g / 10.15 oz. (for standard version)
Display	5.2" IPS LTPS 1920 x 1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, built-in 5000 mAh Standby: over 350 hours Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB 2.0 Type-C, OTG, Type-C headphones supported
Sensors	Light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key

Developing Environment

SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.8 m / 5.91 ft. drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP65 / IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±6 KV conductive discharge

Data Collection

Camera

Rear Camera	13 MP Autofocus with flash
Front Camera (optional)	5 MP camera

Barcode Scanning (optional)

1D Linear Scanner	Zebra: SE965; Honeywell: N4313
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra: SE4710 / SE4750SR / SE4750MR / SE4750DP; Honeywell: N6603
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

HF (optional)

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693
Chips	M1 card (S50/S70), M0 (Ultralight), M3 (Desfire D40/D41/D81), CPU_A card, CPU_B card, iCODE II, TI2048, LRI64K, Others for customization
Range	3-8 cm

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

UHF (optional)

Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
------------------	---

* For detailed specification, please check C71 UHF data sheet

InfraRed (optional)

Frequency	38 kHz
------------------	--------

* For detailed specification, please check C71 InfraRed data sheet

Fingerprint (optional)

Sensor	Capacitive TCS1 / TCS2; Optical Morpho CBM-E3
---------------	---

* For detailed specification, please check C71 Fingerprint data sheet

PSAM (optional)

Card slot	2 slots for PSAM cards
Protocol	ISO7816 T=0, T=1

Accessories

Standard	AC Adaptor, USB Cable, Lanyard, etc.
Optional	Cradle, Holster, etc.

* For detailed specification, please check Accessory Guide.

Notice: Product specifications are subject to change without prior notice. / Model: C71 / Update Date: 2023-02-06

CHAINWAY[®]

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: <http://www.chainway.net>