









1D & 2D

Android

5200 mAh

Megapixel

Laser

3.5" screen

Touchscreen



USB-C





Camera





IP65



4G

4Gેં

WIFI Dual

NFC Bluetooth





drop



Band

2 Years

Warranty



SD35 Leo Speedata

Features

Supports.

1D and 2D barcodes

Software.

Built on Android 8.1

Display.

3.5 inch (640 x 960) high-definition screen

Processor.

Octa core 2.0GHz CPU

Memory.

2GB RAM and 16GB ROM memory

Offers.

Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 4.1, camera, NFC, GSM, WCDMA

Suggested industries















SD35 Leo Technical specifications

Data Capture

Barcode scanning All major symbologies, including AZTEC, CODABAR, CODE11, CODE128, EAN128, CODE39, CODE49, CODE93, COMPOSITE, DATAMATRIX, EAN8, EAN13, INT25, MAXICODE, MICROPDF, PDF417, POSTNET, OCR, QR, RSS, UPCA, UPCE, ISBT, BPO, CANPOST, AUSPOST, IATA25, CODABLOCK, JAPOST, PLANET,

DUTCHPOST, MSI, TLC39, TRIOPTIC, CODE32, STRT25

Performance

Operating System Android 8.1

Octa-core 2.0 GHz Processor

Memory RAM 2GB

16GB Memory Flash

Physical

Audio Front dual stereo speakers, volume 90db ± 3db (test distance 10cm)

Battery Type 5200 mAh

Camera Rear camera 13MP AF, high brightness LED flash

Dimensions (mm) 184 x 70 x 29.8 mm

Display 3.5 inch (640x960), IPS highlight screen

Expected Charge Time PE fast charging, full charge time < 4h

Interfaces 2 Micro SIM card slots, 1 Micro PSAM card slot, 1 Micro SD card slot up to 128GB, USB Type-C, OTG

Keypad 35 buttons, 2 volume buttons, 1 power button, 2 function buttons (1 left, 1 right)

Notifications Sound, vibration, LED prompt

Touch Panel 5-point capacitive touch screen

Weight 290g (with battery)

Wireless

FDD-LTE B1/B3/B7 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 **WWAN RADIO**

CDMA1x/CDMA2000 BC0

WWLAN Radio IEEE 802.11 a/b/g/n 2.4G 5G dual frequency

WPAN RADIO Bluetooth 4.1 BLE

RFID ISO1443A/B, ISO15693, NFC reading distance: 0~5cm

GPS GPS+BD+GLONASS

Environmental

-20°C to +60°C **Operating Temperature**

Storage Temperature -30°C to +80°C

Humidity 5% to 95% (non-condensing)

Electro Static Discharge (ESD) ±16kV air discharge, ±8kV contact discharge

Drop 6 sides can withstand the impact of 1.5 meters drop to concrete

IP65 IP Rating

Certifications

Hardware CCC, CTA, CE, FCC

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

Feel free to contact us or a partner near you



SD35 Leo Technical specifications

Warranty

Standard 2 years

